

FIG. 3
(PRIOR ART)





FIG. 4
(PRIOR ART)






FIG. 5

FIG. 6




FIG. 7




FIG. 8A

```
802
  protocol "IP" {// -----
    len=sizeof(field "Total Length")*8
    / minLen=20*8 //just header
    804 maxLen=65535*8
    header "IP Header"
    806 / payload "IP Payload"
    808 header "IP Header" {// -----
810
  / len=sizeof(field "Header Length")*32
    812 field "Version" 818
    816 field "Header Length" /
    / compound_field "Type Of Service"
    814 field "Total Length"
    824 820
    field "Identification" {len=16 default=291} /
    / compound_field "Flags"
    815 field "Fragment Offset" {len=13 desc="in 64 bits units"} / 822
    field "Time To Live" {len=8 default=30 desc="seconds"} / 826
    / field "Protocol" 830
    828 field "Header Checksum" /
    / field "Source IP Address" {len=32 display=ipv4 field_type=
832 must_encode}
    / field "Destination IP Address" {
834 len=32
    display=ipv4
    field_type = must_encode
    }
  }
```


FIG. 8B

816

```
\repeat {
    len=sizeof(field "Header Length") - 5 ) * 32 // includes padding
    compound_field "Options"
}

field "Version" {
    len=4
    default=4
    possible_values={
        0,15:"Reserved"
        1-3:"Unassigned"
        6-14:"Unassigned"
    }
    4:"IP Internet Protocol"
    5:"ST ST Datagram Mode"
}

field "Header Length" {
    len=4
    minValue=5
    desc="in 32 bit units"
    default=eval_fn(len, "IP", "IP Header", "/32")
}

field "Total Length" {
    minValue=20
    len=16
    desc="in octets include header length"
    default=eval_fn(len, "IP", "IP", "/8")
}

field "Header Checksum" {
    len=16
    default=eval_fn(checksum, "IP", "IP Header")
    display=hex
}
```

FIG. 8C

```
compound_field "Type Of Service" { // . - - - - -
    display=hex
    field "precedence" {
        len=3
        possible_values= {
0:"Routine"
1:"Priority"
2:"Immediate"
3:"Flash"
4:"Flash override"
5:"CRITIC/ECP"
6:"Internetwork Control"
7:"Network Control"
}}

    field "Delay" {
        len=1
        possible_values={0:"normal" 1:"low"}}

    field "Throughput" {
        len=1
        possible_values={0:"normal" 1:"high"}}

    field "Reliability" {
        len=1
        possible_values={0:"normal" 1:"high"}}

    field "Monetary Cost" {
        len=1
        possible_values={0:"normal" 1:"low"}}

    field "Unused" {
        len=1
        possible_values={0:"valid"}}

} // end of field "Type of Service" - - - - -
```

FIG. 8D

```
compound_field "Flags" {
    len=3
    display=hex
field "Reserved" {
    len=1
    possible_values={0:"valid"}}

field "Fragment" {
    len=1
    possible_values={0:"May Fragment" 1:"Don't Fragment"}}
field "Fragments" {
    len=1
    possible_values={0:"last" 1:"more"}}
}

compound_field "Options" {// -----
    optional = (valueof(field "Header Length") > 5)
    compound_field "Option Tuple"
    {
len=8;
display=hex
field "Copied Flag" {
    len=1
    possible_values={0:"not copied into all fragments
0:"not copied into all fragments on fragmentation"
1:"copied into all fragments on fragmentation"
}}
field "Option Class" {
    len=2
    possible_values={
0:"control"
1:"reserved for future use"
2:"debugging and measurement"
3:"reserved for future use"
}}
}}
```

FIG. 8E

```
field "Option Number" {
    len=5
    field_type=mulopt_other_fld
    possible_values={
        0:"end of option list"
        1:"no operation"
        2:"security"
        3:"loose source routing"
        4:"internet timestamp"
        7:"record route"
        8:"stream ID"
        9:"strict source routing"
    }
}

switch(valueof(field "Option Number")){
    0:null
    1:null
    2:compound_field "Security"
    3:compound_field "Loose Source Routing"
    9:compound_field "Strict Source Routing"
    7:compound_field "Record Route"
    8:compound_field "Stream ID"
    4:compound_field "Internet Timestamp"
}

compound_field "Security"{
    len=80
    field "Security Length" {
        len=8
        possible_values={0x0b:"valid"}}}
```

FIG. 8F

```
field "Security: Security"
field "Compartments" {len=16}
field "Handling Restrictions" {len=16}
field "Transmission Control Code" {len=24}

field "Security Security" {
len=16
possible_values={
0:"unclassified"
0xf135:"confidential"
0x0789a:"EFTO"
0xbc4d:"MMMM"
0x5e26:"PROG"
0xaf13:"Restricted"
0xd788:"Secret"
0x6bc5:"Top Secret"
0x35e2,0x9af1,0x4d78,0x24bd,0x135e,0x89af,0xc4d6,0xe26b:
"Reserved for future use"
}}
}

compound_field "Strict Source Routing" {
len=(valueof(field "Strict Source Routing Length")-1)*8
field "Strict Source Routing Length" {len=8 }
field "Strict Source Routing Pointer" {len=8 minValue=4}

repeat {
len=(valueof(field "Strict Source Routing Length")-3)*8
field "source address" {len=32 display=ipv4}
}
}
```

FIG. 8G

```
compound_field "Loose Source Routing" {
  len=(valueof(field "Loose Source Routing Length")-1)*8
  field "Loose Source Routing Length" {len=8 }
  field "Loose Source Routing Pointer" {len=8 minValue=4}
  repeat {
    len=(valueof(field "Loose Source Routing Length")-3)*8
    field "source address" {len=32 display=ipv4}
  }
}

compound_field "Record Routing" {
  len=(valueof(field "Record Routing Length")-1)*8
  field "Record Routing Length" {len=8 }
  field "Record Routing Pointer" {len=8 minValue=4}
  repeat {
    len=(valueof(field "Record Routing Length")-3)*8
    field "source address" {len=32 display=ipv4}
  }
}

compound_field "Stream ID" {
  len=24
  field "Stream ID Length" {
    len=8
    default=4
    possible_values=
      0x04:"valid"
  }
  field "ID" {len=16 default=4}
}
```

FIG. 8H

```
compound_field "Internet Timestamp" {
  field "Internet Timestamp Length" {len=8 }
  field "Internet Timestamp Pointer" {len=8 }
  field "Overflow" {
    len=4
    desc="number of iP modules that cannot register timestamps"
  }
  field "Flag" {
    len=4
    possible_values=1
    0:"time stamps only, stored in consecutive 32-bit words"
    1:"each timestamp is preceded with internet address"
    3:"the internet address fields are prespecified"
  }
}

} // end of Internet Timestamp
} // end of field "option" -----
} // end of field "IP" .-----

field "Protocol" {

len=8
default=255
field_type = mulopt_prctl_fld
display=hex
possible_values={ // -----
  0:"HOPOPT (IPv6 Hop-by-Hop Option)"
  1:"ICMP (Internet Control Message)"
  2:"IGMP (Internet Group Management)"
  3:"GGP (Gateway-to-Gateway)"
```

FIG. 8I

- 4:"IP (IP in IP encapsulation)"
- 5:"ST (Stream)"
- 6:"TCP"
- 7:"CBT"
- 8:"EGP (Exterior Gateway Protocol)"
- 9:"IGP (any private interior gateway)"
- 10:"BBN-RCC-MON (BBN RCC Monitoring)"
- 11:"NVP-II (Network Voice Protocol)"
- 12:"PUP"
- 13:"ARGUS"
- 14:"EMCON"
- 15:"XNET (Cross Net Debugger)"
- 16:"CHAOS"
- 17:"UDP"
- 18:"MUX (Multiplexing)"
- 19:"DCN-MEAS (DCN Measurement Subsystems)"
- 20:"HMP (Host Monitoring)"
- 21:"PRM (Field Radio Measurement)"
- 22:"XNS-IDP (XEROX NS IDP)"
- 23:"TRUNK-1 (Trunk-1)"
- 24:"TRUNK-2 (Trunk-2)"
- 25:"LEAF-1 (Leaf-1)"
- 26:"LEAF-2 (Leaf-2)"
- 27:"RDP (Reliable Data Protocol)"
- 28:"IRTP (Internet Reliable Transaction)"
- 29:"ISO-TP4 (ISO Transport Protocol Class 4)"
- 30:"NETBLT (Bulk Data Transfer Protocol)"
- 31:"MFE-NSP (MFE Network Services Protocol)"
- 32:"MERIT-INP (MERIT Internodal Protocol)"
- 33:"SEP (Sequential Exchange Protocol)"
- 34:"3PC (Third Party Connect Protocol)"
- 35:"IDPR (Inter-Domain Policy Routing Protocol)"
- 36:"XTP (XTP)"

FIG. 8J

- 37: "DDP (Datagram Delivery Protocol)"
- 38: "IDPR-CMTP (IDPR Control Message Transport Protocol)"
- 39: "TP++ (TP++ Transport Protocol)"
- 40: "IL (IL Transport Protocol)"
- 41: "IPv6 (IPv6)"
- 42: "SDRP (Source Demand Routing Protocol)"
- 43: "IPv6-Route (Routing Header for IPv6)"
- 44: "IPv6-Frag (Fragment Header for IPv6)"
- 45: "IDRP (Inter-Domain Routing Protocol)"
- 46: "RSVP (Reservation Protocol)"
- 47: "GRE (General Routing Encapsulation)"
- 48: "MHRP (Mobile Host Routing Protocol)"
- 49: "BNA"
- 50: "ESP (Encap Security Payload for IPv6)"
- 51: "AH (Authentication Header for IPv6)"
- 52: "I-NLSP (Integrated Net Layer Security TUBA)"
- 53: "SWIPE (IP with Encryption)"
- 54: "NARP (NBMA Address Resolution Protocol)"
- 55: "MOBILE (IP Mobility)"
- 56: "TLSP (Transport Layer Security Protocol)"
- 57: "SKIP"
- 58: "IPv6-ICMP (ICMP for IPv6)"
- 59: "IPv6-NoNxt (No Next Header for IPv6)"
- 60: "IPv6-Opts (Destination Options for IPv6)"
- 61: "AHP (Any Host Internal Protocol)"
- 62: "CFTP (CFTP)"
- 63: "ALN (Any Local Network)"
- 64: "SAT-EXPAK (SATNET and Backroom EXPAK)"
- 65: "KRYPTOLAN (Kryptolan)"
- 66: "RVD (MIT Remote Virtual Disk Protocol)"
- 67: "IPPC (Internet Pluribus Field Core)"
- 68: "ADFS (Any Distributed File System)"
- 69: "SAT-MON (SATNET Monitoring)"
- 70: "VISA (VISA Protocol)"

FIG. 8K

- 71:"IPCV (Internet Field Core Utility)"
- 72:"CPNX (Computer Protocol Network Executive)"
- 73:"CPHB (Computer Protocol Heart Beat)"
- 74:"WSN (Wang Span Network)"
- 75:"PVP (Field Video Protocol)"
- 76:"BR-SAT-MON (Backroom SATNET Monitoring)"
- 77:"SUN-ND (SUN ND PROTOCOL-Temporary)"
- 78:"WB-MON (WIDEBAND Monitoring)"
- 79:"WB-EXPAK (WIDEBAND EXPAK)"
- 80:"ISO-IP (ISO Internet Protocol)"
- 81:"VMTP"
- 82:"SECURE-VMTP"
- 83:"VINES"
- 84:"TTP"
- 85:"NSFNET-IGP"
- 86:"DGP (Dissimilar Gateway Protocol)"
- 87:"TCF"
- 88:"EIGRP"
- 89:"OSPF"
- 90:"Sprite-RPC (Sprite RPC Protocol)"
- 91:"LARP (Locus Address Resolution Protocol)"
- 92:"MTP (Multicast Transport Protocol)"
- 93:"AX.25 (AX.25 Frames)"
- 94:"IPIP (IP-within-IP Encapsulation Protocol)"
- 95:"MICP (Mobile Internetworking Control Pro)"
- 96:"SCC-SP (Semaphore Communications Sec. Pro)"
- 97:"ETHERIP (Ethernet-within-IP Encapsulation)"
- 98:"ENCAP (Encapsulation Header)"
- 99:"APES (Any Private Encryption Scheme)"
- 100:"GMTP"
- 101:"IFMP (Ipsilon Flow Management Protocol)"
- 102:"PNNI (PNNI over IP)"
- 103:"PIM (Protocol Independent Multicast)"
- 104:"ARIS"

FIG. 8L

```
105:"SCPS"
106:"QNX"
107:"A/N (Active Networks)"
108:"IPPCP (IP Payload Compression Protocol)"
109:"SNP (Sitara Networks Protocol)"
110:"Compaq-Peer (Compaq Peer Protocol)"
111:"IPX-in-IP"
112:"VRRP (Virtual Router Redundancy Protocol)"
113:"PGM (PGM Reliable Transport Protocol)"
114:"AHOP (Any 0-hop protocol)"
115-254:"Unassigned"
255:"Reserved"
}} // end of field "protocol" - - - - -

    } // end of field "IP header" - - - - -

836  \ payload "IP Payload" { // - - - - -
      / switch(valueof(field "Protocol")) {
838    1:protocol "ICMP"
      2:protocol "IGMP"
      6:protocol "TCP"
      17:protocol "UDP"
      46:protocol "RSVP"
      47:protocol "GRE"
      89:protocol "OSPF"
      }
    } // end of packet "IP payload" - - - - -
  }
```

FIG. 9A

```

*/
/*****
Constants
*****/
//===== LCP Options =====
int OPT_PASSIVE = 1; // Don't die if we don't get a response
int OPT_RESTART = 2; // Treat 2nd OPEN as DOWN, UP
int OPT_SILENT = 4; // Wait for peer to speak first

//===== LCP States =====
int INITIAL_STATE = 0;
int STARTING_STATE = 1;
int CLOSED_STATE = 2;
int STOPPED_STATE = 3;
int CLOSING_STATE = 4;
int STOPPING_STATE = 5;
int REQ_SENT_STATE = 6;
int ACK_RCVD_STATE = 7;
int ACK_SENT_STATE = 8;
int OPENED_STATE = 9;

//===== LCP Events =====
int UP_EVENT = 0;
int DOWN_EVENT = 1;
int OPEN_EVENT = 2;
int CLOSE_EVENT = 3;
int TIMEOUT_POS_EVENT = 4;

```

FIG. 9B

```

int TIMEOUT_NEG_EVENT = 5;
int RCV_CFG_REQ_POS_EVENT = 6;
int RCV_CFG_REQ_NEG_EVENT = 7;
int RCV_CFG_ACK_EVENT = 8;
int RCV_CFG_NACK_EVENT = 9;
int RCV_TERM_REQ_EVENT = 10;
int RCV_TERM_ACK_EVENT = 11;
int RCV_UNKN_CODE_EVENT = 12;
int RCV_CODE_REJECT_POS_EVENT = 13;
int RCV_CODE_REJECT_NEG_EVENT = 14;
int RCV_ECHO_REQ_REPLY_EVENT = 15;

//===== Transition Constants =====
int TRANSITION_CNST_FALSE = 0;
int TRANSITION_CNST_TRUE = 1:

902 fsm "LCP"
{
904 state INITIAL_STATE
926 {
928 UP_EVENT -
OPEN_EVENT InitialStOpenEvent
} // INITIAL
CLOSED_STATE
STARTING_STATE
924 ↗

```

FIG. 9C

```

906 state STARTING_STATE
{
    UP_EVENT
    /
    switch (enabledSilent())
    /
    TRANSITION_CNST_TRUE: StareingStUpEvEnabledSilentTrue
    STOPPED_STATE
    TRANSITION_CNST_FALSE: StareingStUpEvEnabledSilentFalse
    REQ_SENT_STATE
    }
    /
    CLOSE_EVENT
    } // STARTING
908 state CLOSED_STATE
{
    DOWN_EVENT
    /
    switch (enabledSilent())
    /
    INITIAL_STATE

```

FIG. 9D

```

{
    /
    TRANSITION_CNST_TRUE:      ClosedStOpenEvEnabledSilentTRUE
STOPPED_STATE \
    TRANSITION_CNST_FALSE:    ClosedStOpenEvEnabledSilentFALSE
REQ_SENT_STATE \
}
/
RCV_CFG_REQ_POS_EVENT        ClosedStRcvCfgReqPosEv      CLOSED_STATE
RCV_CFG_REQ_NEG_EVENT        ClosedStRcvCfgReqNegEv      CLOSED_STATE
RCV_CFG_ACK_EVENT            ClosedStRcvCfgAckEv          CLOSED_STATE
RCV_CFG_NACK_EVENT           ClosedStRcvCfgNackEv          CLOSED_STATE
RCV_CODE_REJECT_POS_EVENT    RcvCodeRejectPosEv          CLOSED_STATE
RCV_CODE_REJECT_NEG_EVENT    ClosedStRcvCodeRejectNegEv   CLOSED_STATE
RCV_ECHO_REQ_REPLY_EVENT     RcvEchoReqReplyEv           CLOSED_STATE
} // CLOSED
910 state STOPPED_STATE
{
    DOWN_EVENT                StoppedStDownEv            STARTING_STATE
    OPEN_EVENT
    /
    switch(enabledRestart ())
    /
    {
    /
    TRANSITION_CNST_TRUE:      StoppedStOpenEvEnabledRestartTRUE  STOPPED_STATE
    /
    /

```

FIG. 9E

```

    }

    /
    CLOSE_EVENT
    RCV_CFG_REQ_POS_EVENT
    RCV_CFG_REQ_NEG_EVENT
    RCV_CFG_ACK_EVENT
    RCV_CFG_NACK_EVENT
    RCV_CODE_REJECT_POS_EVENT
    RCV_CODE_REJECT_NEG_EVENT
    RCV_ECHO_REQ_REPLY_EVENT
    } // STOPPED

    912 state CLOSING_STATE
    {
        DOWN_EVENT
        OPEN_EVENT
        TIMEOUT_POS_EVENT
        TIMEOUT_NEG_EVENT
        RCV_TERM_ACK_EVENT
        RCV_CODE_REJECT_POS_EVENT
        RCV_CODE_REJECT_NEG_EVENT
        RCV_ECHO_REQ_REPLY_EVENT
    } // CLOSING

        .
        StoppedStRcvCfgReqPosEv
        StoppedStRcvCfgReqNegEv
        StoppedStRcvCfgAckEv
        StoppedStRcvCfgNackEv
        RcvCodeRejectPosEv
        StoppedStRcvCodeRejectNegEv
        RcvEchoReqReplyEv

        CLOSED_STATE
        ACK_SENT_STATE
        REQ_SENT_STATE
        STOPPED_STATE
        STOPPED_STATE
        STOPPED_STATE
        STOPPED_STATE
        STOPPED_STATE
        STOPPED_STATE

        INITIAL_STATE
        STOPPING_STATE
        CLOSING_STATE
        CLOSED_STATE
        CLOSED_STATE
        CLOSING_STATE
        CLOSED_STATE
        CLOSING_STATE

```


FIG. 9F

```

914 __state STOPPING_STATE
    {
        DOWN_EVENT
        CLOSE_EVENT
        TIMEOUT_POS_EVENT
        TIMEOUT_NEG_EVENT
        RCV_TERM_ACK_EVENT
        RCV_CODE_REJECT_POS_EVENT
        RCV_CODE_REJECT_NEG_EVENT
        RCV_ECHO_REQ_REPLY_EVENT
    } // STOPPING

916 __state REQ_SENT_STATE
    {
        DOWN_EVENT
        CLOSE_EVENT
        TIMEOUT_POS_EVENT
        TIMEOUT_NEG_EVENT
        RCV_CFG_REQ_POS_EVENT
        RCV_CFG_REQ_NEG_EVENT
        RCV_CFG_ACK_EVENT
        RCV_CFG_NACK_EVENT
        RCV_CODE_REJECT_POS_EVENT
        RCV_CODE_REJECT_NEG_EVENT
        RCV_ECHO_REQ_REPLY_EVENT
    } // REQ_SENT_STATE

    StoppingStDownEv
    StoppingStTimeoutPosEv
    StoppingStTimeNegEv
    StoppingStRcvTermAckEv
    RcvCodeRejectPosEv
    RcvCodeRejectNegEv
    RcvEchoReqReplyEv

    ReqSentStDownEv
    ReqSentStCloseEv
    ReqSentStTimeoutPosEv
    ReqSentStTimeNegEv
    ReqSentStRcvCfgReqPosEv
    ReqSentStRcvCfgReqNegEv
    ReqSentStRcvCfgAckEv
    ReqSentStRcvCfgNackEv
    RcvCodeRejectPosEv
    RcvCodeRejectNegEv
    RcvEchoReqReplyEv

    STARTING_STATE
    CLOSING_STATE
    REQ_SENT_STATE
    STOPPED_STATE
    ACK_SENT_STATE
    REQ_SENT_STATE
    ACK_RCVD_STATE
    REQ_SENT_STATE
    REQ_SENT_STATE
    STOPPED_STATE
    REQ_SENT_STATE

```

FIG. 9G

```

918 state ACK_RCVD_STATE
{
    DOWN_EVENT      AckRcvdStDownEv
    CLOSE_EVENT      AckRcvdStCloseEv
    TIMEOUT_POS_EVENT AckRcvdStTimeoutPosEv
    TIMEOUT_NEG_EVENT AckRcvdStTimeNegEv
    RCV_CFG_REQ_POS_EVENT AckRcvdStRcvCfgReqPosEv
    RCV_CFG_REQ_NEG_EVENT AckRcvdStRcvCfgReqNegEv
    RCV_CFG_ACK_EVENT AckRcvdStRcvCfgAckEv
    RCV_CFG_NACK_EVENT AckRcvdStRcvCfgNackEv
    RCV_TERM_REQ_EVENT AckRcvdStRcvTermReqEv
    RCV_TERM_ACK_EVENT .
    RCV_UNKN_CODE_EVENT .
    RCV_CODE_REJECT_POS_EVENT RcvCodeRejectPosEv
    RCV_CODE_REJECT_NEG_EVENT RcvCodeRejectNegEv
    RCV_ECHO_REQ_REPLY_EVENT RcvEchoReqReplyEv
} // ACK_RCVD_STATE

920 state ACK_SENT_STATE
{
    DOWN_EVENT      AckSentStDownEv
    CLOSE_EVENT      AckSentStCloseEv
    TIMEOUT_POS_EVENT AckSentStTimeoutPosEv
    TIMEOUT_NEG_EVENT AckSentStTimeNegEv
    STARTING_STATE
    CLOSING_STATE
    REQ_SENT_STATE
    STOPPED_STATE
    OPENED_STATE
    ACK_RCVD_STATE
    REQ_SENT_STATE
    REQ_SENT_STATE
    REQ_SENT_STATE
    REQ_SENT_STATE
    ACK_RCVD_STATE
    REQ_SENT_STATE
    STOPPED_STATE
    ACK_RCVD_STATE
    STARTING_STATE
    CLOSING_STATE
    ACK_SENT_STATE
    STOPPED_STATE

```

FIG. 9




FIG. 9I

CLOSE_EVENT	OpenedStCloseEv	CLOSING_STATE
RCV_CFG_REQ_POS_EVENT	OpenedStCfgReqPosEv	ACK_SENT_STATE
RCV_CFG_REQ_NEG_EVENT	OpenedStRcvCfgReqNegEv	REQ_SENT_STATE
RCV_CFG_ACK_EVENT	OpenedRcvCfgAckEv	REQ_SENT_STATE
RCV_CFG_NACK_EVENT	OpenedStRcvCfgNackEv	REQ_SENT_STATE
RCV_TERM_REQ_EVENT	OpenedStRcvTermReqEv	STOPPING_STATE
RCV_TERM_ACK_EVENT	OpenedStRcvTermAckEv	REQ_SENT_STATE
RCV_CODE_REJECT_POS_EVENT	RcvCodeRejectPosEv	OPENED_STATE
RCV_CODE_REJECT_NEG_EVENT	OpenedStRcvCodeRejectNegEv	STOPPING_STATE
RCV_ECHO_REQ_REPLY_EVENT	RcvEchoReqReplyEv	OPENED_STATE
} // OPENED_STATE		
}		

FIG. 10




FIG. 11




FIG. 12A

1202

Events	State	1	2	3	4	5
	0 Initial	Starting	Closed	Stopped	Closing	Stopping
Up	2	tc1,6	-	-	-	-
Down	-	-	0	1	0	1
Open	1	1	tc1,3/tc2,6	tc3,3r	5r	5r
Close	0	0	2	2	4	4
TO+	-	-	-	-	4	5
TO-	-	-	-	-	2	3
RCR+	-	-	2	8	4	5
RCR-	-	-	2	6	4	5
RCA	-	-	2	3	4	5
RCN	-	-	2	3	4	5
RTR	-	-	2	3	4	5
RTA	-	-	2	3	2	3
RUC	-	-	2	3	4	5
RXJ+	-	-	2	3	4	5
RXJ-	-	-	2	3	2	3
RXR	-	-	2	3	4	5

FIG. 12B

1204

Events	State			
	6	7	8	9
	Req-Sent	Ack-Rcvd	Ack-Sent	Opened
Up	-	-	-	-
Down	1	1	1	1
Open	6	7	8	tc3,9r
Close	4	4	4	4
TO+	6	6	8	-
TO-	3p	3p	3p	-
RCR+	8	9	8	8
RCR-	6	7	6	6
RCA	7	6	9	6
RCN	6	6	8	6
RTR	6	6	6	5
RTA	6	6	8	6
RUC	6	7	8	9
RXJ+	6	6	8	9
RXJ-	3	3	3	5
RXR	6	7	8	9

[p] Passive option

[r] Restart option

[s] Silent option

// Transition conditions

tc1 - (enabledSilent() == TRUE)

tc2 - (enabledSilent() == FALSE)

tc3 - (enabledRestart() == TRUE)

FIG. 13




FIG. 14

FIG. 14A	FIG. 14B
----------	----------




FIG. 14A

1400

FIG. 14B




FIG. 15




FIG. 18




FIG. 16

1600

1610	1602	1604	1606	1608	
	TypeId	TypeName	TableName	Type	Comment
	0	Start		Control	
	0	ProtocolNames	ProtocolNames		
	1	Protocol	Protocol	Compound	
	2	Header	Header	Compound	
	3	Payload	Payload	Compound	
	4	Trailer	Trailer	Compound	
	5	CompountField	CompountField	Compound	
	6	Repeat	Repeat	Compound	
	7	Switch	Switch	Compound	
	8	PossibleValues	PossibleValues	Attribute	
	9	Field	Field	Simple	
	10	Len	Len	Attribute	
	11	MinLen	Len	Attribute	
	12	MaxLen	Len	Attribute	
	13	Display	Display	Attribute	
	14	Encode	Encode	Attribute	
	15	Default	Default	Attribute	
	16	Break	Len	Attribute	
	17	Optional	Len	Attribute	
	18	Offset	Len	Attribute	
	19	Name	Name	Attribute	
	20	Description	Description	Attribute	
1612	21	String	String		
	22	End	End	Control	
	23	DecisiveField	Field	Simple	
	24	FieldType	Attribute	Attribute	
	28	MinVal	Attribute	Attribute	
	29	MaxVal	Attribute	Attribute	
	30	Count	Len	Attribute	

FIG. 17




FIG. 19

1900




FIG. 20

2000




FIG. 21

Protocol	Status	Time	Mode
LCP	Open	09/04/00 08:01:03 AM	Emulate
IPCP	Negotiating	09/04/00 08:01:07 AM	Monitor
MPLSCP	Closed	09/04/00 08:01:05 AM	Monitor
RSVP	N/a	09/04/00 08:01:00 AM	Disabled

FIG. 22

	Rx1	Rx2
Current Status	Open	Negotiating
Loop-back	No	No
Unanswered Echo Requests	0	0
Maximum Receive Unit	512	1500
Asynchronous Character Map	0	0
Authentication Protocol	Unknown	Unknown
Quality Protocol	N/a	N/a
Protocol Field Compression	Off	Off
Address/Control Field Compression	Off	Off
Magic Number	0xFF	0x1FF
FCS Alternative	CCITT 32-bit	CCITT 32-bit

FIG. 23

FIG. 23A
FIG. 23B

FIG. 23A

Time	Recvr	Protocol	MsgType	Event	Synopsis
09/04/00 08:01:01 AM	Rx1	LCP	ConfigReq	Protocol Negotiating	ACComp:On,Pcomp:On,Magic:0x1ab82049
09/04/00 08:01:01 AM	Rx2	LCP	ConfigAck	Open Protocol	ACComp:On,Pcomp:On,Magic:0x4e3d9123
09/04/00 08:01:02 AM	Rx2	LCP	ConfigReq	Protocol Negotiating	ACComp:On,Pcomp:On,Magic:0x1ab82049
09/04/00 08:01:03 AM	Rx1	LCP	ConfigAck	Open Protocol	ACComp:On,Pcomp:On,Magic:0x1ab82049
09/04/00 08:01:04 AM	Rx2	IPCP	ConfigReq	Protocol Negotiating	Local IP: 198.85.38.199
09/04/00 08:01:06 AM	Rx1	IPCP	ConfigAck	Open Protocol	Local IP: 198.85.38.199
09/04/00 08:01:06 AM	Rx1	IPCP	ConfigReq	Protocol Negotiating	Local IP: 198.85.34.35
09/04/00 08:01:06 AM	Rx2	IPCP	ConfigAck	Open Protocol	Local IP: 198.85.34.35
09/04/00 08:01:10 AM	Rx2	MPLSCP	ConfigReq	Protocol Negotiating	
09/04/00 08:01:12 AM	Rx2	MPLSCP	TermReq	Close Protocol	
09/04/00 08:11:01 AM	Rx1	RSVP	Rx1	Rx1	Resv Request <session: 198.85.34.45 UDP port 14>

09/04/00 08:11:03 AM	Rx1	RSVP	Rx1	Rx1	Resv Confirm <session: 198.85.34.45 UDP port 14>
09/04/00 08:11:04 AM	Rx2	RSVP	Rx2	Rx2	Path Request <session: 198.85.38.199 UDD port 0x82A>
09/04/00 08:11:06 AM	Rx1	RSVP	Rx1	Rx1	Resv Error <session: 198.85.38.199 UDP port 0x82A>
09/04/00 09:21:10 AM	Rx2	RSVP	Rx2	Rx2	Path Request <session: 198.85.38.199 UDP port 0x82A>
09/04/00 09:21:12 AM	Rx2	RSVP	Rx2	Rx2	Resv Confirm <session: 198.85.38.199 UPD port 0x82A>
09/04/00 09:21:30 AM	Rx1	RSVP	Rx1	Rx1	Path Tear <session: 198.85.34.45 UPD port 14>
09/04/00 09:21:32 AM	Rx2	RSVP	Rx2	Rx2	Resv Tear <session: 198.85.34.45 UPD port 14>
09/04/00 09:21:32 AM	Rx2	RSVP	Rx2	Rx2	Resv Tear <session: 198.85.34.45 UPD port 14>
09/04/00 11:44:30 PM	Rx1	IPCP	TermReq	Close Protocol	
09/04/00 11:44:31 PM	Rx1	IPCP	TermAck	Close Protocol	
09/04/00 11:44:32 PM	Rx1	LCP	TermReq	Close Protocol	
09/04/00 11:44:33 PM	Rx2	LCP	TermAck	Close Protocol	

FIG. 23B